

LED Warning Trailer with loading ramp AT



Technical Details

Technical details Vehicle

| | |
|-------------------------|--|
| Max. permissible weight | 2500 kg |
| Empty weight | approx. 1100 kg |
| Axles | Double axle trailer |
| Brake | Parking brake and overrun brake |
| Drawbar | Height adjustable, Knott |
| Hitch | DIN towing eye and ballpoint hitch |
| Support wheel | Foldable |
| Chassis | Galvanized steel or Stainless steel (Option) |
| Underride protection | With integrated vehicle illumination |
| Support legs (2 pcs.) | Hydraulic support, cranc support or fall support |
| Loading area | YES |
| Loading ramp | YES |
| Side Panels | YES |
| Batteries | 2 pcs. 12V/ 230 AH |
| Battery charger | 30A |
| Operation Voltage | 12/ 24V (automatic) |
| Vehicle illumination | 12V |
| Stability | 85 km/h stand-alone |
| Vehicle title | EU (AT) |

Control Unit

| | |
|----------------|--|
| Control unit 1 | Radio remote control with feedback signal (Optional) |
| Control unit 2 | Controller installed on the trailer (Backup) |

Technical details Warning Board

| | |
|-----------------------|---|
| Warning board | In compliance with Austrian RVS |
| Approval LED-lamps | Compliant to EN-12352, Cl. L2H and Cl. L8H |
| Night dimming | Automatic |
| Traffic sign | Directional arrow adjustable by electronic actuator |
| Traffic sign foldable | "Working man" and "80 km/h" |
| Signage | Type RA2 red/ white or red/ yellow-fluorescent |
| Lifting/ Lowering | Hydraulic |

Optional Accessories

| |
|--------------------------------------|
| LED beacon |
| Adapter plug 7pol 12V --> 13pol 12V |
| Adapter plug 15pol 24V --> 13pol 12V |

