

LED Warning Trailer with loading ramp INT



Technical Details

Technical details Vehicle

Max. permissible weight	2500 kg
Empty weight	approx. 1100 kg
Axles	Double axle trailer
Brake	Parking brake and overrun brake
Drawbar	Height adjustable, Knott
Hitch	DIN towing eye and ballpoint hitch
Support wheel	Foldable
Chassis	Galvanized steel or Stainless steel (Option)
Underride protection	With integrated vehicle illumination
Support legs (2 pcs.)	Hydraulic support, cranc support or fall support
Loading ramp	YES
Loading area	YES
Side panels	YES
Batteries	2 pcs. 12V/ 230 AH
Battery charger	30A
Vehicle illumination	12/ 24V (automatic)
Vehicle illumination	12V
Stability	85 km/h stand-alone
Vehicle title	EU (AT)

Control Unit

Control unit 1	Radio remote control with feedback signal (Optional)
Control unit 2	Controller installed on the trailer (Backup)

Technical details Warning Board

Warning board	In compliance with German TL Warnleuchten and TL-Absperrtafeln
Approval LED-lamps	Compliant to EN-12352, Cl. L8H and Cl. L9H/ L9M
Night dimming	Automatic
Traffic sign	Directional arrow adjustable by electronic actuator
Signage	Type RA2
Viewing window	Lockable
Lifting/ Lowering	Actuator

Optional Accessories

LED beacon	
Adapter plug 7pol 12V --> 13pol 12V	
Adapter plug 15pol 24V --> 13pol 12V	

