


LED VMS TMA Overhead



Control Unit



Technical Details

Technical details LED VMS Trailer

| | |
|---------------------------------|------------------------------|
| Weight | approx. 1200 kg |
| Frame | Galvanized steel & Aluminium |
| Battery charger | 30A incl. Charge Controller |
| Batteries | 12V/ 720Ah (PzV Premium) |
| Lifting/ Lowering Warning Board | Hydraulic |
| Lifting/ Lowering TMA | Hydraulic |
| Operation Voltage | 12V |

Control Unit

| | |
|----------------|--|
| Control unit 1 | Radio remote control with feedback signal (Optional) |
| Control unit 2 | Controller installed on the trailer (Backup) |

Technical details Warning Lamps

| | |
|--------------------|-------------------------------------|
| Warning lamps | 2 pcs. LED warning lamps |
| Approval LED-lamps | Compliant to EN-12352, Cl. L9H/ L9M |

Technical details Warning Board

| | |
|--------------------|--|
| Warning board | In compliance with German TL-Warnleuchten and TL-Absperrtafeln |
| Approval LED-lamps | Compliant to EN-12352, Cl. L8H and Cl. L9H/ L9M |
| Night dimming | Automatic |

Technical details LED Message Board Top

| | |
|------------------|--|
| Dimensions (WxH) | 2540 x 960 mm |
| Resolution | Gesamt 128 x 48 px (48 x 48 px + 80 x 48 px) |
| Pixel pitch | 20 mm |

Technical details LED Message Board Rear

| | |
|------------------|----------------|
| Dimensions (WxH) | 1280 x 1600 mm |
| Resolution | 64 x 80 px |
| Pixel pitch | 20 mm |

Technical details LED Message Boards

| | |
|-------------------|---|
| LED colors | RGB Fullcolor |
| Programming | Freely programmable |
| Image design | Paint or LED-Image Tool (*.bmp) |
| Night dimming | Automatic |
| Temperature range | from -20°C to +60°C |
| Protection level | IP 54 |
| Approvals | Optical performance in compliance with EN-12966 |

Optional Accessories

| | |
|---|--|
| LED beacon | |
| G.T.M.S. - Global Traffic Management System | |

